



SIZE	L	H ₁	H ₂	W	WEIGHT	QUANTITY
Rc 1/2	80	137	46	65	1.4 kg	
Rc 3/4	90				1.6 kg	
Rc 1	105				1.9 kg	

28	Seat	PTFE	1	
27	Washer	SUS303	1	
26	Name Label	Tetron	1	
25	Push Nut	SUS304	1	
24	Name Plate	SUS304	1	
23	Gasket	PTFE	1	
22	Gasket	Copper	1	
21	Gasket	Copper	1	
20	Gasket	PTFE	1	
19	Taper Pin	SUS303	1	
18	Spring	SUS304	1	
17	Screen	SUS304	1	≈ 20 Mesh
16	Spring	SUS304	1	
14	Adjust Bolt	SUS303	1	
13	Stop Ring	SUS304	1	
12	Shaft	SUS303	1	
11	Orifice Plate	Brass	1	≈ C3771
10	Handle	Plastic	1	
9	Sleeve	SUS303	1	
8	Spring	Special Alloy	1	
7	Holder	C3771	1	
6	Bellows	C5191	1	
5	Valve Seat	SUS304	1	
4	Valve	SUS440C	1	
3	Plug	C3771	1	
2	Cover	A6061	1	
1	Body	C3771	1	

NO.	PART	MAT'L	QUANTITY	REMARKS
	FLUID	STEAM	MAX. TEMP.	204 °C
	PRIM. PRESS.	1.6 MPa	SECOND. PRESS.	0.05~1 MPa
DRN	S.K.	CHKD	—	APPD S.K.
	TYPE	PRESS. REDUCING VALVE		
	MODEL	RE1		
	DWG. NO.	A02781-02		