



(art. 1200 - 1201)

Pressa per termoadesivi

Press for heat-stickers

Presse für thermoaukleber



art. 901 - 120: Tavolo di sostegno - Support table - Stotzbrett
art. 902 - 1202: Telaio di caricamento - Frame - Beladungsrahmen

ART		550	900	1200
Dimensioni Dimensions Abmessungen	cm	50x50	100x50	120x50
W	W	1500	2700	3300
V	V	220 - 380	220 - 380	220 - 380
Tempo di pressione Pressure time Presszeit		0-210"	0-210"	0-210"
Temperatura Temperature range Temperaturekontrolle		0°-210°	0°-210°	0°-210°
Peso Weight Gewicht	kg	75	85	100
Imballo Packaging Verpackung	cm	80x60x55	80x120x55	80x120x55

- All'interno della gamma presse da ricamo, strass, doppio piano riscaldato
The complete range includes the embroidery press, strass press and double heating press
Die Auswahl schließt Stickereipresse, Strass und doppelgewärmtfläche ein
- Funzionamento manuale
Manual operation
Manueller Betrieb
- Interruttore generale magnetotermico
Thermal-magnetic cut-out switch
Thermomagnetischer Hauptschalter
- Centralina elettronica per impostazione tempo e temperatura con segnalazione acustica
Electronic system with timing and temperature setting and acoustic signal
Elektronisch Steuerung mit Temperaturkontrolle und Zeitgeber mit akustischem Signalton
- Regolazione della pressione dei piani
Top pressure regulator
Pressdruck- Reguliervorrichtung
- Operiamo in modo da ridurre al minimo l'impatto ambientale dei nostri prodotti o della nostra attività industriale
We take action to minimize the negative ecological impact of our products and of our industrial activity
wir ergreifen Maßnahmen, um die negative ökologische Auswirkung unserer Produkte und unserer industriellen Tätigkeit herabzusetzen



Tutti gli articoli sono collaudati singolarmente
All products CE are tested and checked individually by our staff
Alle Produkte CE werden von unserem Personal geprüft und überprüft